

Technical Specification for Art 9815 (VW49T)

Product: Viking Mining Boot



Colour	Yellow/ Black
Size Range	EU : 38 – 50 US : 5 – 15
Type of construction	Vulcanized rubber upper and sole 14" tall construction (External height)
Last Sole/Pattern	PSV/ST
Recommendation	 Suitable for mining development For working safely in multiple risk professional environment
Compliance C EN ISO 20345:2022 SB M P E HRO FO	European Standard CE Approved – EN ISO 20345: 2022 (SB M P E HRO FO)
AS 2210.3:2019 SB M P E HRO FO SRA	Australia Standard Approved- AS 2210.3: 2019 (SB M P E HRO FO SRA) SB = Standard Basic Protection as per EN ISO 20345 M = Metatarsal protection SRA = Slip Resistance on ceramic tile with Sodium Lauryl Sulphate FO = Fuel Oil Resistant Outsole E = Heel Energy Absorption P = Nail Penetration Resistance HRO = Resistant to hot contact
C / ASTM	CSA Z195-14 / ASTM F2413-18 Grade 1 Toe protection Compression resistance, 11kN Nail penetration resistance





ASTM F2413-18 M I/C Mt EH PR



Metatarsal protection



18 kV electric shock resistance (ESR) protection











Lining Material	Extra comfort with woven cotton canvas
Upper construction	 Reinforced rubber upper Metatarsal protection at front part Waterproof High visibility with black and yellow contrast Easy for cleaning
Sole / Heel	 Fuel oil resistant sole suitable for inimical environment Slip resistant vulcanized rubber outsole Excellent abrasion resistant for extra durability Heel energy absorption design to minimize heel impact Easy to remove/ wash-off mud and dirt
Steel Toe Cap	 Epoxy coated toe caps for anti-corrosion Meets EN 20345, CSA and ASTM impact and compression tests Metal toecap provides reliable protection in cold & hot environments
Steel Midsole	Non-corrosive stainless steelWithstands pin & sharp objects
Chemical Resistance	 Sole & upper – Good resistant towards acids and alkalis
Finishing	 Lacquer coating for weather protection
Packing	Recyclable Polybag & 3 pairs in a carton

^{*}Specifications of the product are subject to changes without prior notice for further enhancements.

Oct 2023 Rev: 12/YEE















